

FLUORESCENCE MICROSCOPE

VISION PLUS 8000 - FL MAX



Trinocular Observation Head

- Siedentopf observation head inclined at 30° rotatable at 360°.
- Light path selector lever to direct either full light to observation head or 80% to vertical.
- Vertical phototube for digital camera.
- Diopter adjustment ring on ocular tube (± 5).
- Inter-pupillary distance from 48mm to 75mm.

Eyepiece

- Wide field eyepiece 10X (paired) F.O.V. 25mm.

Objectives (Anti fungus coated)

- FLUOR Objective 2X, 4X, 10X, 20X, 40X(SL) and 100X(SL) Oil

Mechanical Body

- Co-axial focusing system with large knobs, PRE-FOCUSING LEVER & TENSION ADJUSTMENT RING.
- Reverse angle sixtuple nosepiece on ball bearing. Slot for Polarizer and DIC.
- Double Plate rackless mechanical stage is 187mmX167mm.
- The mechanical stage has low positioned co-axial controls on ball bearing guide ways.
- Fine division 0.001mm coarse, per rotation, fine stroke 0.1mm per rotation, moving range 24mm

Substage Condenser

- Swing out front lens, N.A. 0.9/1.25, filter holder and iris diaphragm.

Excitation Filters (Optional)

- B Excitation (400-490nm) standard
- G Excitation (510-550nm) standard

Light Source

- Transmitted Kohler light source: 3W LED bulb.
- Epi-Fluorescence light source: 3W high brightness LED lamps. Enable selecting monochromatic or dichromatic LED for light source.

Standard Accessories

- 3W LED, operating manual, dust cover, fuse, guarantee card, blue filter, and styrofoam molded pack